



Olbernhauer Eisenhof GmbH

Am Walzwerk 4 • D-09526 Olbernhau
Tel. (03 73 60) 7 52 98 • Fax (03 73 60) 7 52 97
info@eisenhof.com • www.eisenhof.com

Edelstahl - Rohre



Geschweißte Rohre Werkstoff-Nr.: 1.4301, 1.4541, 1.4571 ca 6 m Hlg
DIN 17455 / 17457, Toleranzen nach DIN 2463

Abmessung	kg/m	Abmessung	kg/m	Abmessung	kg/m
6,0 x 1,0	0,125	26,9 x 1,6	1,014	43,0 x 1,5	1,559
8,0 x 1,0	0,175	2,0	1,247	44,5 x 1,5	1,615
1,5	0,244	2,6	1,582	2,0	2,128
10,0 x 1,0	0,225	28,0 x 1,0	0,676	2,6	2,728
1,5	0,319	1,5	0,995	2,9	3,021
12,0 x 1,0	0,275	2,0	1,302	45,0 x 2,0	2,153
1,5	0,394	30,0 x 1,0	0,726	3,0	3,155
2,0	0,501	1,5	1,070	48,3 x 1,6	1,871
13,0 x 1,0	0,300	2,0	1,402	2,0	2,319
1,5	0,432	2,5	1,722	2,6	2,975
14,0 x 1,0	0,326	3,0	2,028	3,2	3,614
1,5	0,470	32,0 x 1,0	0,776	3,6	4,029
2,0	0,601	1,5	1,146	4,0	4,437
15,0 x 1,0	0,351	2,0	1,502	50,0 x 1,0	1,227
1,2	0,415	3,0	2,178	1,5	1,822
1,5	0,507	33,0 x 1,5	1,183	2,0	2,404
2,0	0,651	33,7 x 1,6	1,286	3,0	3,521
16,0 x 1,0	0,376	2,0	1,588	4,0	4,610
1,5	0,545	2,6	2,025	50,8 x 1,5	1,852
2,0	0,701	2,9	2,237	51,0 x 2,0	2,454
17,0 x 1,0	0,401	3,2	2,444	2,6	3,151
17,2 x 1,6	0,625	3,6	2,713	52,0 x 1,0	1,277
2,0	0,761	4,0	2,975	1,5	1,897
2,3	0,858	34,0 x 1,0	0,826	2,0	2,504
18,0 x 1,0	0,426	1,5	1,221	53,0 x 1,5	1,934
1,5	0,620	35,0 x 1,5	1,258	54,0 x 2,0	2,604
2,0	0,801	2,0	1,653	57,0 x 1,5	2,085
20,0 x 1,0	0,476	2,5	2,035	2,0	2,754
1,5	0,695	36,0 x 2,0	1,703	2,5	3,412
2,0	0,901	38,0 x 1,0	0,926	3,0	4,056
2,5	1,096	1,5	1,371	60,3 x 1,6	2,352
3,0	1,277	2,0	1,803	2,0	2,920
21,3 x 1,6	0,789	2,6	2,305	2,3	3,340
2,0	0,967	3,0	2,629	2,6	3,757
2,6	1,217	40,0 x 1,0	0,977	2,9	4,168
22,0 x 1,0	0,526	1,5	1,446	3,2	4,575
1,5	0,770	2,0	1,903	3,6	5,111
2,0	1,002	2,5	2,348	4,0	5,639
23,0 x 1,5	0,808	3,0	2,779	63,5 x 1,6	2,480
24,0 x 2,0	1,102	4,0	3,606	2,0	3,080
25,0 x 1,0	0,601	42,4 x 1,6	1,635	2,6	3,819
1,5	0,833	2,0	2,023	64,0 x 2,0	3,105
2,0	1,152	2,6	2,591	69,0 x 2,0	3,355
2,5	1,409	3,2	3,141	70,0 x 1,5	2,573
3,0	1,653	3,6	3,498	2,0	3,405
		4,0	3,847	3,0	5,033



Olbernhauer Eisenhof GmbH

Am Walzwerk 4 • D-09526 Olbernhau
Tel. (03 73 60) 7 52 98 • Fax (03 73 60) 7 52 97
info@eisenhof.com • www.eisenhof.com



Geschweißte Rohre Werkstoff-Nr.: 1.4301, 1.4541, 1.4571 ca 6 mHl
DIN 17455 / 17457, Toleranzen nach DIN 2463

Abmessung	kg/m	Abmessung	kg/m	Abmessung	kg/m
76,1 x 1,6	2,985	101,6 x 2,0	4,988	139,7 x 2,0	6,896
2,0	3,711	3,0	7,527	2,6	8,926
2,3	4,250	104,0 x 2,0	5,108	3,0	10,269
2,6	4,785	108,0 x 2,0	5,308	4,0	13,592
2,9	5,315	3,0	7,888	154,0 x 2,0	7,612
3,2	5,841	3,2	8,397	159,0 x 3,0	11,720
3,6	6,535	4,0	10,417	4,0	15,525
4,0	7,222	114,3 x 2,0	5,624	168,3 x 2,0	8,328
80,0 x 1,5	2,948	2,5	6,998	3,0	12,417
2,0	3,906	3,0	8,361	4,0	16,456
3,0	5,784	3,2	8,902	219,1 x 2,0	10,872
84,0 x 2,0	4,107	3,6	9,979	3,0	16,233
85,0 x 2,0	4,157	4,0	11,048	4,0	21,544
88,9 x 1,6	3,498	129,0 x 2,0	6,360	5,0	26,805
2,0	4,352	133,0 x 3,0	9,766	273,0 x 3,0	20,290
2,3	4,980	4,0	12,921	323,9 x 3,0	24,100
2,6	5,618				
2,9	6,245				
3,2	6,876				
4,0	8,504				

Fettgedruckte Abmessungen auch in 1.4301 geschliffen,
240 Korn und Folie lieferbar.
Nahtlose Rohre auf Anfrage.

Geschweißte kalibrierte Konstruktions- und Dekorationsrohre ungebeizt K0 W.Nr. 1.4301

nach DIN 17455 für allgemeine Anforderungen, nicht wärmebehandelt
von 8 x 1,0 bis 168,3 x 3,0 mm, auch in geschliffener Ausführung Korn 220/240

Geschweißte hitzebeständige Rohre

W.Nr. 1.4828, 1.4720, 1.4512, andere Werkstoffe auf Anfrage

Geschweißte Getränkeleitungsrohre nach DIN 11850 Reihe 1 und 2

W.Nr. 1.4301, 1.4571, 1.4404

von 18 x 1,0 bis 204 x 2,0 mm in den Ausführungen BC, CC, CD und BD

Geschweißte Handlaufrohre poliert

W.Nr. 1.4301

20 x 1,5, 22 x 1,5, 23 x 1,5, 25 x 1,5 und 2,0, 30 x 1,5 und 2,0, 40 x 2,0

Flachovalrohre

blank, W.Nr. 1.4301, 1.4404

60 x 33 x 2,0

Geschweißte Rohrbogen W.Nr. 1.4571, DIN 2605, Norm 3 S 90°

Klöpferböden W.Nr. 1.4571, DIN 28011